

COMO series

A perfect combination between aesthetics and functionality.



Versatile and multi -functions

- Street and roadway lighting
- Walkway, parks and garden illumination
- Industrial areas illumination




Mechanical

- Die-casting aluminium housing
- 5mm ultra-clear tempered glass
- Silicon gasket
- Stainless steel bolts
- Highly polished aluminium reflector

Technical Specifications

- Power: 30 - 120W
- 90 - 305VAC input voltage
- 10KV surge protection
- Switch disconnection
- 100lm/w luminaire efficiency
- IP66
- IK08
- Class I or class II

Dimension



Mounting: C

P

S

Product Code	CM - 30W	CM - 50W	CM - 60W	CM - 80W	CM - 90W	CM - 100W	CM - 120W
LED Qty	14	24	28	36	40	44	56
Total Power consumption	30W	50W	60W	80W	90W	100W	120W
Input Voltage	90~305V AC	90~305V AC	90~305V AC	90~305V AC	90~305V AC	90~305V AC	90~305V AC
CCT(K)	2700K~7000K	2700K~7000K	2700K~7000K	2700K~7000K	2700K~7000K	2700K~7000K	2700K~7000K
CRI	Ra>70	Ra>70	Ra>70	Ra>70	Ra>70	Ra>70	Ra>70
Luminaire Flux (lumen)	3000	5000	6000	8000	9000	10000	12000



**INNOVATIVE
TRAFFIC SOLUTIONS**
Subsidiary of Traffic Technologies Ltd

