



Quantum LED Floodlight

Designed for ultimate versatility, Quantum LED floodlight delivers precise control offering a choice of symmetrical and asymmetrical distributions. Its streamlined design, high performance and maximised visual comfort complements any exterior space, and makes this floodlight the first choice for a host of commercial applications. Built tough for Australian & New Zealand condition. COMPACT | FLEXIBLE | EFFICIENT | RAPIX READY.

- Available in 200W and 300W versions
- Latest LED chip configuration
- Integral driver standard with 0-10V dimming capabilities, making the Quantum LED suitable for RAPIX control systems
- Supplied with 5-core 1m fly lead for easy connection

LED

5
YEAR
WARRANTY*

DIMMABLE



GENERAL SPECIFICATION

COLOUR TEMPERATURE	CRI	DIMMABLE	IP RATING	IK RATING	FINISH	COLOUR	BEAM ANGLE
4000K	70	Yes	IP66	IK06	Powdercoated	Black	120

VOLTAGE	TILT	CHIP CONFIGURATION	HEAT SINK MATERIAL	LAMP TYPE	OPERATING TEMPERATURE (MAX)	WINDAGE
240V	60°	PCOB	Aluminium (Die Cast)	LED (PCBA)	40°C	0.19

UNIQUE SPECIFICATION

ITEM CODE	DESCRIPTION	WATTAGE	LUMEN OUTPUT	DIMENSIONS H x W x L (MM)	BEAM DISTRIBUTION	LUMEN MAINTENANCE
PPH1A5740ET	QUANTUM LED FLOOD 300W IP65 A5 4000K CRI70 1M FLYING LEAD	300W	34544Lm	138 x 324 x 610	Asymmetric	
PPH1S8740ET	QUANTUM LED FLOOD 300W IP65 S8 4000K CRI70 1M FLYING LEAD	300W	32583Lm	138 x 324 x 610	Symmetric	70
PPM1A5740ET	QUANTUM LED FLOOD 200W IP65 A5 4000K CRI70 1M FLYING LEAD	200W	26000Lm	138 x 324 x 610	Asymmetric	70
PPM1S8740ET	QUANTUM LED FLOOD 200W IP65 S8 4000K CRI70 1M FLYING LEAD	200W	24000Lm	138 x 324 x 610	Symmetric	70

Quantum LED Floodlight

ITEM CODE	CIRCUIT WATTAGE
PPH1A5740ET	320W
PPH1S8740ET	320W
PPM1A5740ET	220W
PPM1S8740ET	220W

PRODUCT IMAGES



LINE DRAWINGS

