


Last information update: December 2019

**Joburg - Pole-mounted system for urban and residential parks and gardens****Product code**  
E026**Technical description**

Outdoor luminaire with an elliptical optic, designed to use LED lamps. The optical assembly and the pole attachment system are made of EN1706AC 46100LF aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. Diffusor made of shockproof, UV-stabilised injection moulded polycarbonate. Complete with circuit fitted with Neutral White monochrome LEDs. Optical assembly consisting of an anodized super-pure aluminium upper reflector, a methacrylate lens and a lower reflector made of metallised PC. Replaceable LEDs and driver. Middle of the Night selv driver with automatic internal temperature control system. Overvoltage protection up to 8kV. All external screws are made of stainless steel.

**Installation**

The luminaire can be installed with a pole-top mounting on poles with  $\varnothing$  60mm and 76mm end part using X102 and X126 accessories. Secured to the pole by two bolts.

**Dimension (mm)**

Ø323x190

**Colour**

Grey (15)

**Weight (Kg)**

3


**Mounting**

pole-top

**Wiring**


The product is supplied wired and with an outlet cable (2x1mm) 500mm long.

Complies with EN60598-1 and pertinent regulations

**Product configuration: E026****Technical data**

lm system:	2080	Life Time LED 3:	41,000h - L90 - B10 (Ta 40°C)
W system:	20.18	Life Time LED 4:	100,000h - L80 - B10 (Ta 40°C)
lm source:	-	Ballast losses [W]:	3.4
W source:	-	Lamp code:	LED
Luminous efficiency (lm/W, real value):	102	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	97	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	100	Ambient operating temperature range:	from -40°C to 40°C.
Beam angle [°]:	98° / 110°	Power factor:	On request
CRI:	80	Inrush current:	22 A / 250 µs
Colour temperature [K]:	4000	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 15 luminaires B16A: 24 luminaires C10A: 24 luminaires C16A: 40 luminaires
MacAdam Step:	2	Minimum dimming %:	10
Life Time LED 1:	52,000h - L90 - B10 (Ta 25°C)	Overvoltage protection:	10kV Common mode & 6kV Differential mode
Life Time LED 2:	100,000h - L80 - B10 (Ta 25°C)	Control:	Middle of the night

**Polar**



**Isolux**

