

CONSUMER DATA RIGHT (CDR) CONSULTATION – PART 1 – VARIOUS MINOR AMENDMENTS

PROCEDURE CONSULTATION

SECOND STAGE PARTICIPANT RESPONSE TEMPLATE

Participant: CitiPower Powercor

Submission Date: 15 August 2022

Table of Contents

- 1. Context 3
- 2. Feedback on proposed minor amendments 3

1. Context

This template is to assist stakeholders in giving feedback about the changes detailed in the second draft procedures associated with the Part 1 – Minor Amendments part of the consultation.

2. Feedback on proposed minor amendments

Document	Participant Comments
1. For the enumerations lists in the procedures document, values such as 'Sample Tested' and 'Three-Phase Three-Limb', to be changed from mixed case to uppercase, to improve implementation and validation for both AEMO and Industry.	
2. For the Voltage Transformer Type enumerations, to remove descriptions where they exist in brackets e.g. 'CVT (Capacitive Voltage Transformer)	
3. Where Ratio enumerations exist, remove spaces between characters e.g. '3300 : 110' to '3300:110'	
4. 'INFORMATION' and 'STATISICAL' are to be truncated to 'STATIS' and 'INFORM' to fit within the 'USE' field 10 character max limit.	
5. Alignment of character requirements across aseXML and the Standing Data for MSATs MSATS document by including a reference to the Australian Standards requirements, where relevant in the document applicable.	
6. For the correction of the GPSCoordinates format, implemented inas part of the r42 schema, to be reflected in the Standing Data for MSATs document: CATS_Meter_Register- Browser Cross Reference table.	

Document	Participant Comments
<p>7. For the truncated CurrentTransformerRatioAvailable and CurrentTransformerRatioConnected element names to be reflected in Table 4 CATS_Meter_Register – Browser Cross Reference.</p>	
<p>8. For the VoltageTransformerTest aseXML path to be corrected to ElectricityMeter/VoltageTransformerTest in table 4 CATS_Meter_Register – Browser Cross Reference.</p>	
<p>9. For GPS Coordinates of 0.00000 (5-7 decimal places), to align with the format specified in the NMI Standing Data Procedure, to be applied where no GPS coverage is available at the metering installation.</p>	<p>CitiPower Powercor opposes this change as sending a value of 0.0000000 causes unnecessary changes to participants systems and has the same effect as a sending 0.</p> <p>We did not provide this feedback in the initial round of the consultation but have have since undertaken further analysis and believe the change is unnecessary.</p>
<p>10. For the inclusion of missing Transformer Valid Values to be added to the Standing Data for MSATS document and for all values to be formatted from smallest to largest.</p>	
<p>11. The CATS Procedures to be updated to ensure that 'Meter Manufacturer' and 'Meter Model' are only required when the status code is 'C' (Current) for CR3050 and CR3051 transactions (CiP_061).</p>	
<p>12. For the CATS Procedures to be updated to remove the CR6500/1 Change ROLR Completed Notification from the Change ROLR section to align with the WIGS Procedures</p>	
<p>13. For the CATS Procedures to be updated for CRs (5001 & 5021) to include the NMI Classification of NCONUML as a classification code that have objections raised on it</p>	

Document	Participant Comments
14. Update the WIGS procedure for CR5021 to allow the ENLR (LR) to object.	
15. Update the WIGS procedure to include BULK and XBOUNDARY to CR1500 to allow the MDP to send it to complete the CR.	